SmartLF SCi series

THE HIGH-VOLUME WORKHORSE

Get the job done fast, with no stopping or waiting. The SmartLF SCi delivers high quality and speed for everyday scanning tasks.



0	
◡	
₹	
G.	
~	
12-20	
20	
~	
V1.0	

Option	Monochrome	Color	Enhanced	Monochrome	Color	Enhanced	
Model name	SCi 36m	SCi 36c	SCi 36e	SCi 42m	SCi 42c	SCi 42e	
Imaging technology		SingleSensor			SingleSensor		
Maximum scan width		36 in (914 mm)		42 in (1067 mm)			
Maximum media width	38 in (965 mm) 44 in (1118 mm)						
Scanning speed of full width document:							
200 dpi monochrome		13 in/sec (330 mm/sec)		13 in/sec (330 mm/sec)			
200 dpi color		6 in/sec (152 mm/sec)	12 in/sec (305 mm/sec)		6 in/sec (152 mm/sec)	12 in/sec (305 mm/sec)	
Color upgradeable	Yes	Yes		Yes	Yes		
Productivity in batch scanning ISO AO/Arch	E-size (or widest) for 60) minutes. Includes par	er load and eject time.	Measured in completed	d scans:		
Portrait, 200 dpi	375 docs/hour	261 docs/hour	364 docs/hour	375 docs/hour	261 docs/hour	364 docs/hour	
Specifications:							
Maximum media thickness	0.08 in (2 mm) for flexible documents						
Maximum optical resolution	1200 dpi						
Maximum resolution	9600 dpi (SmartWorks Imaging, SmartWorks Pro), 1200 dpi (SmartWorks Touch)						
Total number of pixels	43200 52800						
Colortrac key technologies	SingleSensor, SureDrive						
Document justification	Left and right (SmartWorks Imaging, SmartWorks Pro). Centre only (SmartWorks Touch)						
Accuracy	0.1% +/-1 pixel						
Data capture color depth inside scanner	48-bit color, 16-bit monochrome						
Color spaces	Adobe RGB, Device RGB, sRGB						
Maximum image length	JPEG 65535 lines. PDF, TIF any length up to 4 GB						
USB interface	USB 3.0 and USB 2.0						
Bundled software	SmartWorks Touch, SmartConnect (drivers, TWAIN, maintenance)						
Optional software	SmartWorks Imaging, SmartWorks Pro						
File formats	TIF, JPG, PNG, PDF, PDF/A, DWF, CALS, BMP, JPEG-2000(JP2), JPEG2000 Extended (JPX), TIF-G3, TIF-G4 and others						
File compatibility	AutoCAD (as raster), CAD, GIS and other raster image editing/storage applications						
Printer support	HP, Canon, Epson and Océ printers. See the full list here: www.colortrac.com/iprinters						
Operating systems	Windows Server 2019 64-bit, Windows 10 and Windows 8.1, 64-bit and 32 bit						
Power consumption	53 W/1.35 W/0.16 W (scanner off, ext. power supply on)						
External power supply	100~240 VAC auto-sensing +/-10%, 50-60Hz						
Operating conditions (environmental)	10–35°C, 35–80% relative humidity (non-condensing)						
Weight	Unpacked: 53 lbs. (24 kg). Packed: 60 lbs. (27.5 kg)			Unpacked: 58.4 lbs. (26.5 kg). Packed: 68.3 lbs. (31 kg)			
Dimensions W×H×D	Unpacked: 45.1×6.0×15 in (115×15.2×38.1 cm)						
Certifications/compliance	CE, cUL/UL, CCC, EAC, BIS, FCC Class A, ICES, EMC, VCCI, KC, EuP, WEEE, RoHS, REACH and ENERGY STAR® certified						
Optional floor stand with basket	Yes						
Optional PC add-on kit for floor stand	Yes						
Optional repro stand	Yes. Height settings: 39/40.8/43/45 in (988/1038/1093/1143 mm)						
Maximum monitor weight and size	13 lbs. (6 kg), 21.5 in (546 mm)						
Country of origin	Designed and engineered in Denmark, Europe. Manufactured in China.						

Tablet not included.

Colortrac is a Global Scanning UK Ltd brand. Colortrac makes no warranty of any kind with respect to the information contained in this document and reserves the right to change specifications without notice. Colortrac and SmartLF® are trademarks of Colortrac. All other trademarks are the property of their respective owners.

Whether your workflow is scanning, archiving, enhancement or copying, SmartWorks Imaging is the best choice for you.

With the new preset engine, you can easily save your settings to create new personal presets for all your originals.

For copying solutions many more printer drivers have been added making the decision over which printer to use very easy.

Combine it with SmartWorks Imaging Link tablet app and boost your productivity even further.



Contact us to request a quote.



